



F1150 small wood stove shown with nickel accent door & bottom heat shield with black cast iron legs.

FEATURES

- Large fire viewing area, with heat radiating ceramic glass
- Wood-finished handle
- Heavy-duty cast hinges that will never bend or break
- Solid forged steel adjustable cam lock ensures a tight door seal over time
- Front-mounted air adjustment
- Air operating safety tool
- High-performance brick-lined firebox reflects heat
- Non-obtrusive air wash curtain keeps glass clean
- Heavy gauge steel log retainers to stop logs from rolling
- Welded ash lip will never bend or break
- Rear heat deflector allowing for closer clearances
- Mobile home and alcove approved

OPTIONS

- Cast iron door with heat radiating ceramic glass in black or nickel accent
- Pedestal base
- Bottom heat shield with cast iron legs in black or brushed nickel
- Ash drawer with cover
- Variable-speed blower
- Convector airmate
- Outside air kit
- Mobile home kit (Canada only)

SPECIFICATIONS

Maximum BTU*	55,000
Typical sq. ft. heated**	600 - 1,200
EPA Efficiency	75% LHV / 70% HHV
Max log size	18"
Burn time	Up to 8 hours
Emissions	1.7 g/h
Firebox size	1.3 cu. ft.
Flue size	6"

* Length of burn time and BTU range depend on type of wood, moisture content, climate conditions and installation.

Refer to page 15 for BTU calculation method.
 ** Varies depending on home floor plan, house layout, heat loss of the house and quality/moisture content of wood.





F1500 shown with cast iron legs and door with nickel accent.

FEATURES

- Large fire viewing area, with heat radiating ceramic glass
- Wood-finished handle
- Heavy-duty cast hinges that will never bend or break
- Solid forged steel adjustable cam lock ensures a tight door seal over time
- Front-mounted air adjustment & catalytic bypass
- Air & bypass safe operation tool
- Easy-to-read catalytic thermometer helps your stove reach maximum burn times & efficiency
- High-performance brick-lined firebox reflects heat
- Non-obtrusive air wash curtain keeps glass clean
- Heavy gauge steel log retainers to stop logs from rolling
- Welded ash lip will never bend or break
- Rear heat deflector allowing for closer clearances
- Mobile home and alcove approved
- 10-year, 100% coverage on the original catalyst

OPTIONS

- Cast iron door with heat radiating ceramic glass in black or nickel accent
- Pedestal base
- Bottom heat shield with cast iron legs in black or brushed nickel
- Ash drawer with cover
- Variable-speed blower
- Convector airmate
- Outside air kit
- Mobile home kit (Canada only)

SPECIFICATIONS

Maximum BTU*	55,000
Typical sq. ft. heated**	600 - 1,200
EPA Efficiency	84% LHV / 77.70% HHV
Max log size	18"
Burn time	Up to 10 hours
Emissions	1.0 g/h
Firebox size	1.3 cu. ft.
Flue size	6"

* Length of burn time and BTU range depend on type of wood, moisture content, climate conditions and installation.

Refer to page 15 for BTU calculation method.
 **Varies depending on home floor plan, house layout, heat loss of the house and quality/moisture content of wood.



INCLUDES 10-YEAR
 100% ORIGINAL
 COMBUSTOR COVERAGE



F2450 medium wood stove shown with black cast iron door & pedestal.

FEATURES

- Large fire viewing area, with heat radiating ceramic glass
- Wood-finished handle
- Heavy-duty cast hinges that will never bend or break
- Solid forged steel adjustable cam lock ensures a tight door seal over time
- Front-mounted air adjustment
- Air operating safety tool
- High-performance brick-lined firebox reflects heat
- Non-obtrusive air wash curtain keeps glass clean
- Welded ash lip will never bend or break
- Rear heat deflector allowing for closer clearances
- Mobile home and alcove approved

OPTIONS

- Cast iron door with heat radiating ceramic glass in black or nickel accent
- Pedestal base
- Bottom heat shield with cast iron legs in black or brushed nickel
- Ash drawer with cover
- 2-speed blower
- Convector airmate
- Outside air kit
- Mobile home kit (Canada only)

SPECIFICATIONS

Maximum BTU*	75,000
Typical sq. ft. heated**	1,000 - 2,200
EPA Efficiency	78.4% LHV / 73.3% HHV
Max log size	18"
Burn time	Up to 10 hours
Emissions	2.3 g/h
Firebox size	2.3 cu. ft.
Flue size	6"

* Length of burn time and BTU range depend on type of wood, moisture content, climate conditions and installation.

Refer to page 15 for BTU calculation method.
 ** Varies depending on home floor plan, house layout, heat loss of the house and quality/moisture content of wood.





F2500 shown with pedestal base and black cast iron door and airmate.

FEATURES

- Large fire viewing area, with heat radiating ceramic glass
- Wood-finished handle
- Heavy-duty cast hinges that will never bend or break
- Solid forged steel adjustable cam lock ensures a tight door seal over time
- Front-mounted air adjustment & catalytic bypass
- Air & bypass safe operation tool
- Easy-to-read catalytic thermometer helps your stove reach maximum burn times & efficiency
- High-performance brick-lined firebox reflects heat
- Non-obtrusive air wash curtain keeps glass clean
- Welded ash lip will never bend or break
- Rear heat deflector allowing for closer clearances
- Mobile home** and alcove approved
- 10-year, 100% coverage on the original catalyst

**Approved in USA only

OPTIONS

- Cast iron door with heat radiating ceramic glass in black or nickel accent
- Pedestal base
- Bottom heat shield with cast iron legs in black or brushed nickel
- Ash drawer with cover
- 2-speed blower
- Convector airmate
- Outside air kit

SPECIFICATIONS

Maximum BTU*	78,000
Typical sq. ft. heated**	1,000 - 2,200
EPA Efficiency	81% LHV / 76% HHV
Max log size	18"
Burn time	Up to 12 hours
Emissions	1.0 g/h
Firebox size	2.3 cu. ft.
Flue size	6"

* Length of burn time and BTU range depend on type of wood, moisture content, climate conditions and installation.

Refer to page 15 for BTU calculation method.

**Varies depending on home floor plan, house layout, heat loss of the house and quality/moisture content of wood.



INCLUDES 10-YEAR
100% ORIGINAL
COMBUSTOR COVERAGE



F3500 shown with pedestal base, contemporary cast iron door and airmate.

FEATURES

- Large fire viewing area, with heat radiating ceramic glass
- Heavy-duty cast hinges that will never bend or break
- Solid forged steel adjustable cam lock ensures a tight door seal over time
- Front-mounted air adjustment & side mounted catalytic bypass
- Easy-to-read catalytic thermometer helps your stove reach maximum burn times & efficiency
- High-performance brick-lined firebox reflects heat
- Non-obtrusive air wash curtain keeps glass clean
- Welded ash lip will never bend or break
- Rear heat deflector allowing for closer clearances
- Mobile home and alcove approved
- 170° opening door for easy loading
- Heavy-duty 3/16 in. steel firebox
- 10-year, 100% coverage on original catalyst

OPTIONS

- Ash drawer with cover
- 2-speed blower
- Convector airmate
- Outside air kit
- Mobile home kit (Canada only)

SPECIFICATIONS

Maximum BTU*	75,000
Typical sq. ft. heated**	1,500 - 2,500
EPA Efficiency	87% LHV / 81% HHV
Max log size	20"
Burn time	Up to 24 hours
Emissions	0.9 g/h
Firebox size	3.0 cu. ft.
Flue size	6"

* Length of burn time and BTU range depend on type of wood, moisture content, climate conditions and installation.

Refer to page 15 for BTU calculation method.

** Varies depending on home floor plan, house layout, heat loss of the house and quality/moisture content of wood.



INCLUDES 10-YEAR
100% ORIGINAL
COMBUSTOR COVERAGE



F5200 shown with pedestal base and black cast iron door and airmate.

FEATURES

- Large fire viewing area, with heat radiating ceramic glass
- Heavy-duty cast hinges that will never bend or break
- Solid forged steel adjustable cam lock ensures a tight door seal over time
- Front-mounted air adjustment & side mounted catalytic bypass
- Easy-to-read catalytic thermometer helps your stove reach maximum burn times & efficiency
- High-performance brick-lined firebox reflects heat
- Non-obtrusive air wash curtain keeps glass clean
- Welded ash lip will never bend or break
- Rear heat deflector allowing for closer clearances
- Mobile home and alcove approved
- 170° opening door for easy loading
- Heavy-duty 3/16 in. steel firebox
- 10-year 100% coverage on the original catalyst

OPTIONS

- Ash drawer with cover
- 2-speed blower
- Convector airmate
- Outside air kit

SPECIFICATIONS

Maximum BTU*	80,000
Typical sq. ft. heated**	1,500 - 3,000
EPA Efficiency	86% LHV / 80% HHV
Max log size	22"
Burn time	Up to 30 hours
Emissions	0.9 g/h
Firebox size	4.4 cu. ft.
Flue size	8"

* Length of burn time and BTU range depend on type of wood, moisture content, climate conditions and installation.

Refer to page 15 for BTU calculation method.
 ** Varies depending on home floor plan, house layout, heat loss of the house and quality/moisture content of wood.



INCLUDES 10-YEAR
 100% ORIGINAL
 COMBUSTOR COVERAGE